


\varnothing_A mm	\varnothing_A O/D mm	\varnothing_A I/D mm	Rolled Edge (nom. mm.)	Galvanised Steel	
100	98	97	6	0.7	
125	124	123	6		
140	139	138	6		
150	148	147	6		
160	159	158	6		
180	179	178	8		
200	200	199	8		
224	224	223	8		
250	250	249	8		
300	298	297	10		
315	313	312	10		
350	348	347	10		0.9
400	400	398	10		
450	449	447	10		
500	499	497	10		
560	559	557	10		
630	629	627	10		
710	709	707	10		



No. of connections (from 2 to 8) and shape (round or rectangular) must be specified when ordering

Construction

Seam: longitudinal seam is lapped, spot welded, and caulked.

Ends

Standard QF end can be changed to Raw ID (I/D), Raw OD (O/D), Hose Adapter (FX), Flat Bar Flange (FL), or 6mm turned out edge (FB).

Temperature Rating of Product Components		
°C	Suction Hood	Sealants
200°	Galvanised Steel	
121°		Joka Seal Metal Sealant 2315
-20°		Joka Seal Metal Sealant 2315

Additional Notes
At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C.

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
Suction Hood	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Acetone blend	AAMA Specification 801.1